

# Safety Data Sheet

## 500ppm Silver Nail Polish

December 23, 2019

### Section 1: Chemical Product and Company Identification

**Product name:** 500 PPM Silver Nail Polish  
**Contact Info:** PPM Silver Cosmetics, LLC  
PO Box 1330  
Salina, 74365  
Info@ppmSilverCosmetics.com  
SilverNailPolish.com  
1-918-919-0269

**Emergency Phone Number:** +1-918-919-0269

### Section 2: Hazards Identification

#### 2.1 - CLASSIFICATION OF THE SUBSTANCE OR MIXTURE



**GHS02; FLAMMABLE**



**GHS07; IRRITANT**

H225 – Highly flammable liquid and vapor. Vapors form from this product and may travel or be moved by air currents and ignited by pilot lights, other flames, sparks, heaters, electrical equipment, static discharges or other ignition sources at locations distant from product handling point. This material may produce a floating fire hazard.

#### 2.2 - LABEL ELEMENTS



**GHS02; FLAMMABLE**



**GHS07; IRRITANT**

#### RISK PHRASES

H225 Highly flammable liquid and vapor  
H319 Cause serious eye irritation  
H336 May cause drowsiness and dizziness

### **PRECAUTIONARY STATEMENTS**

P210 Keep away from heat / sparks / open flames / hot surfaces / - No smoking

P243 Take precautionary measures against static discharge.

P305 + 351 + 338 IF IN EYES: Rinse continuously with water for several minutes. Remove contact lenses if present and easy to do - continue rinsing.

### **2.3 - OTHER HAZARDS**

The mixture contains no substance conforming to the PBT / vPvB criteria of REACH Regulation.

## **Section 3: Composition/Information on Ingredients**

### **3.1 – MIXTURE**

#### **CHEMICAL CHARACTERIZATION**

Nitrocellulose with nitrogen content < 12.2% and at a concentration < 20% in a blend of solvents.

#### **HAZARDOUS COMPONENTS**

<b>Ingredient CAS #</b>	<b>Hazard Symbol (CE) No. 1272/2008</b>	<b>Hazard Symbol 67/548/CEE or 1999/45/CE</b>	<b>Concentration</b>	<b>Registration Number</b>
BUTYL ACETATE CAS: 123-86-4	FLAM. LIQ. 3 H226 ACUTE TOX. 3 H226	R10, R66, R67	32.0 – 43.0 %	01-2119485493-29-XXXX
ETHYL ACETATE CAS: 141-78-6	FLAM. LIQ. 2 H225 EYE IRRIT. 2 H319 ACUTE TOX. 3 H336	F R11 Xi R36, R66, R67	12.0 – 20.0 %	01-2119475103-46-XXXX
NITROCELLULOSE CAS: 9004-70-0	FLAMMABLE LIQUID 1 H224	F R11	11.0 – 15.0 %	POLYMER
ISOPROPYL ALCOHOL CAS: 67-63-0	FLAM LIQ. 2 H225 EYE IRRIT. 2 H319 STOT SE 3 H336	F R11 Xi R67	5.0 – 6.0 %	01-2119457558-25-XXXX

#### **ADDITIONAL INFORMATION**

For the wording of the listed risk phrases refer to Section 16 of this Safety Data Sheet

## **Section 4: First Aid Measures**

### **4.1 – DESCRIPTION OF FIRST AID MEASURES**

**SKIN CONTACT:** Remove contaminated clothing and wash before reuse. Remove and destroy contaminated shoes. Flush with plenty of water.

**INHALATION:** Remove to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Get medical attention.

**INGESTION:** Get medical attention IMMEDIATELY.

**EYE CONTACT:** Immediately wash the eyes with plenty of water for at least 10 minutes holding the eye open. Get medical attention.

#### **4.2 – MOST IMPORTANT SYMPTOMS AND EFFECTS, BOTH ACUTE AND DELAYED**

##### **EFFECTS OF OVEREXPOSURE**

Cause eye irritation. Harmful if swallowed. May cause nose and throat irritation. Causes skin irritation. May affect the brain or nervous system, causing dizziness, headache or nausea. Harmful if inhaled.

##### **OTHER EFFECTS OF OVEREXPOSURE MAY INCLUDE**

Narcosis, conjunctivitis, loss of coordination, vomiting, lacrimation, redness and swelling of eyes, difficulty with speech, reduced visibility, abdominal pain, swelling and redness of skin, fatigue, cough, dermatitis, drowsiness, unconsciousness.

##### **PRIMARY ROUTE(S) OF ENTRY**

Inhalation, skin contact, eyes.

**MEDICAL CONDITIONS THAT CAN BE AGGRIVATED:** N/A

##### **CHRONIC HEALTH HAZARDS**

##### **REPEATED OVEREXPOSURE TO THIS PRODUCT MAY CAUSE**

Lung damage, liver abnormalities, kidney damage, central nervous system damage, blood effects.

In accordance with 29CFR1910.1200, this product contains no ingredients listed by NTP, IARC or OSHA as carcinogenic.

**NOTICE:** Reports have associated repeated and prolonged overexposure to solvents with permanent brain and nervous system damage. Intentional misuse by deliberately concentrating and inhaling the contents of this package may be harmful or fatal.

#### **4.3 IMMEDIATE MEDICAL ATTENTION AND SPECIAL TREATMENT NEEDED**

No further relevant information available.

## **Section 5: Fire-Fighting Measures**

#### **5.1 – EXTINGUISHING MEDIA**

Foam, Carbon Dioxide or Dry Chemical

#### **5.2 – SPECIAL FIREFIGHTING PROCEDURES**

Water may be ineffective in fighting fire. If water is used to cool closed container to prevent pressure build-up, fog nozzles are preferred. Full protective equipment, including self-contained breathing apparatus is needed to protect firefighters from exposure to coating's hazardous ingredients and hazardous decomposition products.

#### **5.3 – FOR FIREFIGHTERS**

During emergency conditions, overexposure to decomposition products may cause a health hazard; symptoms may not be immediately apparent. Obtain medical attention.

## **Section 6: Accidental Release Measures**

#### **6.1 – PERSONAL PRECAUTIONS**

Avoid contact with the skin and the eyes. Keep away from heat and sources of ignition. Provide adequate ventilation.

#### **6.2 – ENVIRONMENTAL PRECAUTIONS**

Prevent further leakage or spillage. Do not discharge into the drains / surface waters / groundwater.

### **6.3 – METHODS FOR CLEANING UP**

Soak up with inert absorbent material (e.g. sand, silica gel, acid binder, universal binder, sawdust). Keep in suitable, closed containers for disposal. Dispose of in accordance with local regulations.

### **6.4 – ADDITIONAL INFORMATION**

Consult trained personnel. Consider the information for “Personal Protection” in Section 8 of this Safety Data Sheet.

## **Section 7: Handling and Storage**

### **7.1 – PRECAUTIONS FOR SAFE HANDLING**

When using, do not eat, drink or smoke. Take off all contaminated clothing immediately. Wash hands before breaks and immediately after handling the product. Provide sufficient air exchange and / or exhaust in work rooms.

### **7.2 – PRECAUTIONS FOR SAFE STORAGE**

Store in well-ventilated area. Keep containers (solvent resistant) closed when not in use. Store away from ignition sources. All equipment should be grounded. Avoid strong oxidizing agents, store in a clean, dry area.

### **7.3 – OTHER PRECAUTIONS**

All precautions must be observed. Empty container may retain product residues (vapor or liquid).

## **Section 8: Exposure Controls/Personal Protection**

### **8.1 – EXPOSURE LIMITS**

<b>Ingredient</b>	<b>CAS #</b>	<b>Description</b>	<b>Value</b>	<b>Unit</b>	<b>Comments</b>
<b>BUTYL ACETATE (Acetic Acid, Butyl Ester)</b>	<b>123-86-4</b>	Vapor Pressure	15.0	mm / Hg	25 °C
		Vapor Pressure	45.0	mm / Hg	50 °C
		PEL-TWA	150.0	ppm	
		TLV-STEL	200.0	ppm	15 Minutes
		PEL-STEL	200.0	ppm	15 Minutes
<b>ETHYL ACETATE</b>	<b>141-78-6</b>	Vapor Pressure	100.0	mm / Hg	27 °C
		Vapor Pressure	200.0	mm / Hg	42 °C
		PEL-TWA	400.0	ppm	
<b>ISOPROPANOL (Isopropyl Alcohol)</b>	<b>67-63-0</b>	Vapor Pressure	40.0	mm / Hg	23.8 °C
		Vapor Pressure	100.0	mm / Hg	39.5 °C
		PEL-TWA	400.0	ppm	
		TLV-STEL	500.0	ppm	15 Minutes
		PEL-STEL	500.0	ppm	15 Minutes

### **8.2 - PERSONAL PROTECTION**

**RESPIRATORY PROTECTION** - Wear an appropriate, properly fitted respirator (NOISH / MSHA approved) during application and handling unless air monitoring demonstrates vapor / mist levels below applicable limits. Follow respirator manufacturer’s recommendations for selection and use.

**VENTILATION** - Sufficient ventilation must be provided to maintain airborne concentrations below TLV, PEL and LEL limits as listed in Section 8.

**PROTECTIVE GLOVES** - Chemical resistant protective gloves (such as Neoprene or Butyl rubber) should be worn when handling this product. Check with glove manufacturer to determine proper glove type.

**EYE PROTECTION** - Splash proof chemical goggles should be worn.

**OTHER PROTECTIVE EQUIPMENT** – Impervious clothing and boots should be worn. Eye bath and safety shower should be provided.

**HYGENIC PRACTICES** - Good personal hygiene practices are required at all times when handling chemicals. These practices include, but are not limited to, washing when safety equipment is removed, at the end of each shift or when going on breaks especially if contamination occurs.

## Section 9: Physical and Chemical Properties

<b>FORM</b>	Viscous liquid		
<b>COLOR</b>	Colorless (Clear)		
<b>ODOR</b>	Fruity (Esters)		
<b>OLFACTIVE THRESHOLD</b>	50 ppm (Ethyl Acetate)		
<b>MELTING POINT</b>	-84 °C (Ethyl Acetate)		
<b>BOILING POINT</b>	77 °C (Ethyl Acetate)		
<b>BOILING RANGE</b>	77 to 130 °C		
<b>SPECIFIC GRAVITY</b>	0.98 – 1.020		
<b>VAPOR PRESSURE (hPa)</b>	100 (20 °C) (Ethyl Acetate)		
<b>VAPOR DENSITY (Relative: Air = 1)</b>	3.04 (Ethyl Acetate)		
<b>FLASH POINT</b>	-5 °C		
<b>AUTO IGNITION TEMPERATURE</b>	460 °C		
<b>FLAMMABLE LIMITS (% v/v)</b>		<b>Upper</b>	<b>Lower</b>
<b>BUTYL ACETATE</b>		7.6	1.7
<b>ETHYL ACETATE</b>		11.0	2.2
<b>ISOPROPANOL</b>		12.0	1.8
<b>PH</b>	Not applicable		
<b>SOLUBILITY IN WATER</b>	Insoluble		
<b>WATER / OCTANOL DISTRIBUTION COEFF.</b>	Log Kow = 0.60 (Ethyl Acetate)		
<b>EVAPORATION RATE</b>	Slower than ether		
<b>VISCOSITY (Brookfield)</b>	600 to 1100 mPa.s		

## Section 10: Stability and Reactivity

### **10.1 - REACTIVITY**

Material is STABLE under non-emergency conditions.

### **10.2 - CHEMICAL STABILITY**

Material WILL NOT undergo hazardous polymerization.

### **10.3 - HAZARDOUS REACTION**

Not known.

### **10.4 - CONDITIONS TO AVOID**

Heat, sparks, open flame.

#### **10.5 - MATERIALS TO AVOID**

Sodium hydroxide, nitric acid, oxidizers, acids, alkali, metal, amines.

#### **10.6 - HAZARDOUS DECOMPOSITION PRODUCTS**

Methane, oxides of nitrogen. Carboxylic acids, various hydrocarbons, oxides of carbon, aldehydes, hydrogen cyanide, acids.

### **Section 11: Toxicological Information**

This product has NOT been tested on animals to obtain toxicology data. Toxicology data for the components of this product can be found in scientific literature, but this data has not been presented in this document.

#### **INGESTION**

Important: Ingestion can cause nausea and a great narcosis with weakness, drowsiness and loss of consciousness.

#### **INHALATION**

Can cause irritation of the nose and throat. At high concentration, can cause narcosis.

#### **CONTACT WITH THE SKIN**

Prolonged contact can cause cracks in skin

#### **CONTACT WITH THE EYES**

Can cause irritation of the conjunctive. Can cause injury of the cornea.

### **Section 12: Ecological Information**

Any release of this product into sewers or streams must be avoided.

#### **WATER HAZARD CLASS**

WGK1: Slightly hazardous for water.

### **Section 13: Disposal Conditions**

Incinerate in a furnace where permitted under Federal, State and Local regulations.

### **Section 14: Transport Information**

#### **ROAD TRANSPORT**

Technical Name	PAINT (Source of danger: Ethyl Acetate, Ethyl Acetate, Nitrocellulose, Isopropyl Alcohol)
ADR Class	3
ADR Pack Group	II
Tunnels Restriction Code	D/E
Danger Label	3
Kemler Number	33
UN Number	1263

### **MARITIME TRANSPORT**

Technical Name	PAINT (Source of danger: Ethyl Acetate, Ethyl Acetate, Nitrocellulose, Isopropyl Alcohol)
UN Number	1263
IMDG Class	3
Marine Pollutant	No
Ems Number	F-E, <u>S-D</u>
IMDG Pack Group	II
Danger Label	3
Flash Point	-5 °C
Other indications relative to Maritime Transport:	
-Not viscous product as per IMDG code 2.3.2.5	
-Limited Quantity 5L/30 kg (gross)	
Certified Packaging:	Internal packaging: metal, glass, plastic External packaging: carton 4G

### **IATA**

Technical Name	PAINT (Source of danger: Ethyl Acetate, Ethyl Acetate, Nitrocellulose, Isopropyl Alcohol)
UN Number	1263
IATA Class	3
Danger Label	3
Pack Group	II
Packing Instr.	353 (Passenger) – Maximum Quantity 5L 364 (Cargo) – Maximum Quantity 60L

## **Section 15: Regulatory Information**

No other data.

## **Section 16: Other Information**

### **RELEVANT PHRASES**

H224	Extremely flammable liquid and vapor
H225	Highly flammable liquid and vapor
H226	Flammable liquid and vapor
H302	Harmful if swallowed
H315	Causes skin irritation
H318	Causes serious eye damage
H319	Causes serious eye irritation
H335	May cause respiratory irritation
H336	May cause drowsiness and dizziness
R10	Flammable
R11	Highly Flammable
R22	Harmful if swallowed
R36	Irritating to eyes

R37/ 38	Irritating to respiratory system and skin
R41	Risk of serious damage to eyes
R66	Repeated exposures may cause skin dryness and cracking
R67	Vapors may cause drowsiness and dizziness

The information in this publication is believed to be accurate and is given in good faith, but no representation of warranty as to its completeness or accuracy is made. Suggestions for uses or applications are only opinions. Users are responsible for determining the suitability of these products for their own particular purpose. No representing of warranty, expressed or implied, is made with respect to information or products including, without limitation, warranties or merchantability, fitness for a particular purpose, non-fringement of any third party patent or other intellectual property rights including, without limit, copyright, trademark and design.